

**902-928 MHz FORKLIFT MOUNT 6dBic CP RFID PANEL ANTENNA**

The Laird Technologies' S9026X antenna gives RFID users an antenna that meets all of the criteria requirements for forklift RFID applications. At only 7.6" x 7.6" x .95", the antenna is small enough to accommodate a wide variety of forklift applications. The antenna provides 6dBi of gain in the 902-928 MHz band.

The antenna material construction is unique in that it is an all metal antenna. No exterior radome enclosure is required to protect critical components. The result is an antenna that is extremely robust and resistant to damage.

The antenna can be mounted directly to the forklift allowing for a view directly into any pallet. Two antennas can be mounted side by side on a custom configured mounting platform if that is desirable.

The antenna is provided with a plastic front panel that is secured with adhesive for the purposes of providing a surface that can be used for branding or for any other graphical element that the customer might desire.

**FEATURES** 

- Low profile
- Extremely low VSWR
- Wide band
- Weather resistant radome
- Wide range of connector and cable options
- Left hand and right hand CP versions

**APPLICATIONS**

- Direct forklift mount
- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyor belt


**global solutions: local support.™**

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com


Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)



Right-hand circularly polarized linear azimuth plot



Right-hand circularly polarized linear elevation plot

#### SPECIFICATIONS

Antenna Part Number	S9026X
Frequency Range	902 - 928 MHz
Gain	6 dBic
Maxium VSWR	1.5:1
3 dB Beamwidth - Azimuth	80°
Front to Back Ratio	10 dB
Polarization	Circular Right-hand
Maxium Input Power	4 Watts
Input Impedence	50 Ohms
Axial Ratio	3 dB
Weight (Kg)	2.6 lbs (1.2)
Mechanical Size	7.59" x 7.59" x .95"
Antenna Connection	Right Angle Type N Male
Radome	Aluminum / Grey UV Polycarbonate
Mount Style	Chassis mount
Temperature Operational	-25°C to +70°C
Lightning Protection	DC Grounded

ANT-DS-S9026X 0409

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request. All Laird Technologies' products are sold pursuant to the Laird Technologies' domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© 2009 All Rights Reserved  
Laird Technologies is a registered trademark of Laird Technologies, Inc.